

ASSEMBLING & INSTALLATION INSTRUCTIONS

The drawing shown may not exactly match the product enclosed. However, the installation instructions do apply to this product.

28034

- WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.
- ATTENTION! COUPER LE COURANT AU FUSIBLE OU UN DISJONCTEUR.


ASSEMBLING THE FIXTURE (Fig.1)

- 1. Shut off the power at the circuit breaker and remove old fixture, including the single bar.
- 2. Carefully unpack your new fixture and lay out all the parts on a clear area. Take care not to lose any small parts necessary for installation.
- 3. **NOTE**: Discharge of the screws(C), remove the shade(A).
- 4. Install the light bulb(No Included) in accordance with the fixture's specifications. NOTE: DO NOT EXCEED THE MAXIMUM WATTAGE RATING!
- Raise the lamp holder(B) insert to the shade(A), lock it securely with screws(C).
- 6. Attach the assembly lamp body onto the post (No included) and lock it securely with the screws(D).

CONNECTING THE WIRES (Fig.2)

- 1. Connect the electrical wires as follows. Connect the Black wire from the fixture to the black (hot) house Wire. Connect the white wire from the fixture to the white (neutral) house wire. Connect the supply ground wire (green or bare copper) with fixture's ground wire to it. Make sure all wire nuts are secured. You may wrap the connections with electrical tape.
- 2. Tuck the wire connections neatly into the post.

Your installation is now complete. Return power to the junction box and test the fixture.



©COPYRIGHT ALL RIGHTS RESERVED. LIVEX LIGHTING, INC.